

Mini Pro 300 V and Mini 500 V generators

- At constant voltage or constant current
- Selection in 1 V or 1 mA increments
- LED display
- 2 outputs
- Compact and lightweight
- Timer 1 to 999 minutes or continuous with alarm function
- Polycarbonate case, aluminium base



Model	Mini Pro 300 V generator	Mini 500 V generator
Power	60 W 10-400mA 10-300 V	120 W 10-400mA 10-500 V
Operating temperature	Ambient temperature at + 40 °C	Ambient temperature at + 40 °C
Dimensions (mm)	13x 189 x 85	140 x 191 x 84
Weight	0,9 kg	NC
Minuteur	1 to 999 minutes with alarm	1 to 999 minutes with alarm
Cat. No.	022099	022237
€ Excl. VAT	NC -	NC -

MyVolt mini Power supply

Constant voltage (V)	100 or 200
Max. current (mA)	200
Max. power (W)	40
Output Terminals	2
Power supply	230 - 240 V, 50 - 60 Hz
Dim. W x D x H (cm)	16 x 11.5 x 5.7
Weight (g)	400
Cat.No.	062693
€ Excl. VAT	NC -

- Ultra-compact two-output generator
- Basic device for constant voltage application
- 2 constant voltages to choose from, 100 or 200 V



MyVolt touch Power supply

- For agarose or acrylamide gel electrophoresis
- Intuitive programming
- Can be positioned horizontally or vertically
- Touch screen with automatic rotation
- Constant voltage or constant current mode
- Overload, change of load and no load detection
- Stackable unit

Current (mA)	5 to 400
Current increment (mA)	5
Voltage (V)	10 to 300
Voltage increment (V)	5
Max power (W)	80
Timer	1 min to 99 h 59 min
Output Terminals	4
Screen size (mm)	50.8 x 50.8
Power supply	230 V, 50 Hz
Dim. (cm) W x D x H	21.5 x 15.5 x 9.75
Weight (kg)	1.6
Cat.No.	062694B
€ Excl. VAT	NC -

