

Calibrex Dispensers



Calibrex® Dispenser  
530 solutae

Calibrex® Dispenser  
525 organo

- Choice of dispensing volume by graduated slider on both sides
- Integrated calibration system
- Autoclavable assembled (at 121°C)
- 360° rotation of the dispenser
- The parts in contact with the liquid are chemically inert
- Correctness (Rel. Err. %): Min vol.  $\leq \pm 1.5\%$ , med vol.  $\leq \pm 1.1\%$ , max vol.  $\leq \pm 0.6\%$
- Accuracy (CV %): Min vol.  $\leq \pm 0.5\%$ , med vol.  $\leq \pm 0.35\%$ , max vol.  $\leq \pm 0.1\%$

- Delivered with :
  - base 45 mm diameter;
  - cap and spout: 90 mm for 1 to 10 ml models / 120 mm for 25 to 100 ml models ;
  - suction hose 350 mm ;
  - three connections : GL 28, 32 and 40 for 1 to 10 ml models / GL 32, 38 and 40 for 25 to 100 ml models ;
  - calibration certificate and operation manual
- Warranty: 2 years

**Calibrex® 530 solutae Dispensers/ 1 ml to 100 ml**

Borosilicate glass cylinder, piston with PFA coating. Suitable for saline solutions, strong and weak acids and bases. Red.

Volume (ml)	Division (ml)	Without tap		With tap	
		Cat.No.	€ Excl. VAT	Cat.No.	€ Excl. VAT
0.1 - 1	0.02	061995	NC -	061999	NC -
0.25 - 2.5	0.05	061996	NC -	062000	NC -
0.5 - 5	0.1	061997	NC -	350342	NC -
1 - 10	0.2	061998	NC -	350343	NC -
2.5 - 25	0.5	061842	NC -	061953	NC -
5 - 50	1	061843	NC -	061954	NC -
10 - 100	1	061844	NC -	061955	NC -

**Calibrex® 525 organo Dispenser / 1 ml to 100 ml**

Frosted glass piston, borosilicate glass cylinder. Suitable for organic solutions, non-crystallising acids and basic solutions. Yellow.

Vol. (ml)	Division (ml)	Spout Length (mm)	Supplied with neck adapters	Without tap		With tap	
				Cat.No	€ Excl. VAT	Cat.No	€ Excl. VAT
0.1 - 1	0.02	90	GL 28, GL 32, GL 40	061987	NC -	061991	NC -
0.25 - 2.5	0.05			061988	NC -	061992	NC -
0.5 - 5	0.1			061989	NC -	061993	NC -
1 - 10	0.2			061990	NC -	061994	NC -
2.5 - 25	0.5	120	GL 32, GL 38, GL 40	061845	NC -	061950	NC -
5 - 50	1			061846	NC -	061951	NC -
10 - 100	1			061847	NC -	061952	NC -



Version with tap

See accessories on [www.dulis.nl](http://www.dulis.nl)



Calibrex 520 digital dispensers



- Adjustable volume pre-calibrated dispenser
- Quick and precise selection of each volume
- Dispenser can rotate 360°
- Can be quickly dismantled without tools
- Autoclavable fully assembled
- High impact and chemical resistance
- Glass cylinder and piston with PFA coating
- Easy calibration by the user

**Calibrex 520 digital dispensers / 2 ml, 5 ml and 10 ml**

3 models in a volume range from 0.25 to 10 ml. The instrument can be screwed directly onto laboratory bottles thanks to its standard thread of 32 mm and its 3 adapters (28, 40, 45 mm).

Fixed volume			Variable volume			
Cat.No	Volume (ml)	€ Excl. VAT	Cat.No	Volume (ml)	Division (ml)	€ Excl. VAT
061281	2	NC -	061018	0.25 - 2	0.05	NC -
061282	5	NC -	061019	1 - 5	0.1	NC -
061283	10	NC -	061020	1 - 10	0.25	NC -

Accessories

CatNo.	Description	€ Excl. VAT
985191	Telescopic FEP suction tube 150 - 255 mm	NC -
985192	Telescopic FEP suction tube 195 - 345 mm	NC -
061074	Extension for Calibrex 520 and 521 (20 ml)	NC -
061024	Calibrex 520 dispenser holder up to 50 ml	NC -
061025	Remote sample holder 50 ml	NC -
061026	Remote sample holder 100 ml	NC -

See fittings on [www.dulis.nl](http://www.dulis.nl)

