

Simport® Microtubes



| | |
|----------------------------|---|
| Volume (ml) | 1.5 |
| Material | Polypropylene |
| Sterile | No |
| Cap Type | Snap Secure-Lock™ ; pierceable |
| Autoclavable | Yes |
| Max. centrifugal speed (g) | 20000 |
| Graduation | Yes |
| Marking area | Yes |
| Operating temperature | -175 °C to +121 °C |
| Specifications | Secure locking system to prevent accidental opening; free of DNases, RNases, DNA and endotoxins |
| Units/box | Resealable bag of 500 microtubes |
| Cat. No. | 040210 |
| € Excl. VAT/box | NC - |



4Titude Microtubes



| | |
|----------------------------|---|
| Volume (ml) | 2 |
| Material | Polypropylene |
| Caps | Yes |
| Cap Type | Safe-Lock Snap |
| Autoclavable | Yes |
| Max. centrifugal speed (g) | 20000 |
| Graduation | Yes |
| Marking area | Yes |
| Specifications | Secure locking system to prevent accidental opening; free of DNases, RNases, DNA and endotoxins |
| Units/box | Bag with 500 microtubes |
| Cat. No. natural | 448067 |
| € Excl. VAT/box | NC - |



Hamilton microtubes



| | | | |
|---------------------------|---|------------------------------------|---|
| Volume (ml) | 1.5 | | |
| Material | Polypropylene | | |
| Sterile | No | No | Yes |
| Caps | Yes | | |
| Cap Type | Snap opening at the back of the cap / self-locking cap at 90 °C | | |
| Autoclavable | Yes | | |
| Max centrifugal speed (g) | 15000 | 15000 | 15000 |
| Graduation | Yes | | |
| Marking area | Yes | | |
| Operating temperature | -80 °C to +121 °C | | |
| Specifications | - | Free of DNase, RNase and endotoxin | Free of DNases, RNases, human DNA, endotoxins, ATP and PCR inhibitors |
| Units/box | 4 bags with 500 microtubes | 4 bags with 500 microtubes | 20 bags with 100 microtubes |
| Cat. No. natural | 199204 | 199205 | 199206 |
| € Excl. VAT/box | NC - | NC - | NC - |

