

Microwtube® With seal screw cap Simport®

	Flat								
Flat									
Volume (ml)	0.5			1.5					
Diameter (mm)	11								
Height (mm)	44								
Material	Polypropylene								
Sterile	No	Yes	Yes	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip								
Autoclavable	Yes								
Max centrifugal speed (g)	17000	17000	17000	20000	20000	20000	17000	17000	17000
Skirt	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes	No	No	Yes
Marking area	Yes								
Operating temperature	-196 °C to +121 °C								
Specifications	Cap with seal for a perfect seal; no release agents, plasticizers or biocides; Free of DNase, Rnase, DNA and endotoxins; Tested at 95 KPa								
Units/box	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes
Cat. No. natural	039151	039156	039270	039152	039157	039309	039153	039158	039308
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -

	Flat					
Flat						
Volume (ml)	2					
Diameter (mm)	11					
Height (mm)	44					
Material	Polypropylene					
Sterile	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip					
Autoclavable	Yes	Yes	Yes	Yes	Yes	Yes
Max centrifugal speed (g)	20000	20000	20000	17000	17000	17000
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes
Marking area	Yes					
Operating temperature	-196 °C to +121 °C					
Specifications	Cap with seal for a perfect seal; no release agents, plasticizers or biocides; Free of DNase, Rnase, DNA and endotoxins; Tested at 95 KPa					
Units/box	1000 microtubes	500 microtubes	500 microtubes	1000 microtubes	500 microtubes	500 microtubes
Cat. No. natural	039154	039159	039312	039155	039160	039311
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -