

## DURAN® PURE Bottles

- Developed for the pharmaceutical industry
- In accordance with the recommendations of the international pharmacopoeia
- Borosilicate glass type I EP/USP
- Coating to prevent contamination
- Certificate of analysis available per batch
- Full traceability
- 100% visual control
- Drug master file type III

### ➤ Applications

- Production of pharmaceutical products
- Storage of drug intermediates
- Transport of APIs



Volume (ml)	Neck Ø (thread)	Units/box	Transparent		Amber		Neck Ø (thread)	Transparent		Amber	
			Cat. No.	€/box	Cat. No.	€/box		Cat. No.	€/box	Cat. No.	€/box
25	GLS 25	10	096971	NC -	096979	NC -	-	-	-	-	-
100	GLS 45	10	096972	NC -	096980	NC -	-	-	-	-	-
250	GLS 45	10	096973	NC -	096981	NC -	-	-	-	-	-
500	GLS 45	10	096974	NC -	096982	NC -	GLS 80	096997	NC -	097003	NC -
1000	GLS 45	10	096942	NC -	096983	NC -	GLS 80	096998	NC -	097004	NC -
2000	GLS 45	10	096975	NC -	096984	NC -	GLS 80	096999	NC -	097005	NC -
5000	GLS 45	1	096976	NC -	096985	NC -	GLS 80	097000	NC -	097006	NC -
10000	GLS 45	1	096977	NC -	096986	NC -	GLS 80	097001	NC -	097007	NC -
20000	GLS 45	1	096978	NC -	096987	NC -	GLS 80	097002	NC -	097008	NC -

## Duran® PREMIUM bottles with ring and cap in TPCH

- GL 45 thread and traceability code
- High security containers corresponding to USP/EP/FDA standards
- Equipped with a ring and a cap with PTFE-coated silicone seal
- For use from -196 °C to + 260 °C
- Accuracy of the scale ±5%, for filling and quantifying spill volumes
- Ideal for sterilisation processes (hot air and dry sterilisation) and depyrogenation
- Supplied complete with translucent cap

Cat. No.	Capacity (ml)	Units/box	€/box
091376	100	10	NC -
091377	250	10	NC -
091378	500	10	NC -
091379	1000	10	NC -

### Pouring ring and cap

Cat. No.	Description	Units/box	€/box
091205	Pouring ring	5	NC -
090387	Cap with seal	5	NC -



Enter the Cat. No. on [dulis.nl](http://dulis.nl) to find our procedure for autoclaving and treating laboratory glassware.



GLASSWARE

## Duran® Thick-walled Bottles

- Borosilicate glass 3.3 type 1
- Ideal for stirring and mixing processes with large and heavy dip tubes
- Reinforced walls
- With traceability code
- Do not contain EGS/TSE hazardous materials
- Can be depyrogenated, autoclaved and sterilised
- Standard thread (GL45) or wide neck (GLS80) version
- Supplied without cap and pouring ring

Cat. No.	Volume (l)	DIN (GL) thread	Diameter (mm)	Height (mm)	€
083480	10	45	228	410	NC -
083481	10	80	228	385	NC -
083477	20	45	289	505	NC -
083478	20	80	289	480	NC -

