MM Series Semi-Rigid Heating Mantles

>230V - 50-60 Hz

>Security class o

≻IP 30

- >Steel case, epoxy paint
- >Thermal insulation with ceramic fibre
- **≻**Thermoregulation
- ➤With ON/OFF button

€	N/A -				
Cat. No.	396000	396001	396002	396003	396004
Weight (kg)	1.5	1.5	1.8	2.4	5
Dimensions (øxH in mm)	185 x 145	185 x 145	205 X 150	245 X 175	310 X 210
Heating capacity (W)	130	180	250	450	600
Accuracy °C	± 5	± 5	± 5	± 5	± 5
Temperature °C	350	350	350	350	450
Flasks capacity (ml)	100	250	500	1000	2000
Flask diameter (mm)	64	85	105	131	166



Spotflam

- ➤ Flame pen
- ➤ Flame temperature: 1 750 °C
- Heating temperature adjustable with one hand
- ➤ Autonomy of more than 5 hours
- Supplied with C360 cartridge (Cat. No. 060311)
- ➤ Supplied with a soldering iron tip

Cat. No.	Description	€
071129	Spotflam	66.N/A -
060311	Butane gas cartridge 52 g CV360 (the 6)	N/A -



Safe alcohol lamp

- >Screwed candle ring
- Alcohol volume: 100 ml
- >Flask width: 7.5 cm
- ➤Total height with cap: 9.5 cm
- ➤ Supplied complete with wick, candle ring, cap, flask



Cat. No.	Description	€
068811	Complete alcohol lamp	N/A -
068812	Spare wick	N/A -

FlameBoy

The FlameBoy is a flaming gun with piezoelectric ignition. It is available in two versions, one that can be connected to a central gas supply, the other using gas cartridges so that it can be used independently. The FlameBoy is particularly well suited to on-site sterilisation.

Cat. No.	Description	€
060400	FlameBoy with threaded connector	N/A -
060401	FlameBoy with adapter for gas cartridge	N/A -

Accessories for FlameBoy

Cat. No.	Description	Units/ cardboard box	€/ cardboard box
060410	Adapter for cartridge connection for independent use	1	N/A -
060311	Butane gas cartridge 52 g CV360	6	N/A -



Matches

Practical, in a box of 240.

Cat. No.	Description	€ the 3 x 240
006791	Box of Matches	N/A -

