

TFX410 Thermometers



- Removable probe
- Model with or without cable
- Various probe lengths
- Easy to use
- Temperature range: -50 to +300°C
- Accuracy: ± 0.3°C
- Resolution : 0.1 °C
- IP 67
- Dimensions W x thickness x H (mm): 54 x 22 x 109
- Weight (g): 90

Model	TFX410												TFX410-1				
Probe	Pt1000	TPX 400-40	TPX 400-150	TPX 440	TPX 100-20	TPX 100-30	TPX 100-40	TPX 200-20	TPX 200-30	TPX 200-40	Without	TPX 400	TPX 100	TPX 200	TPX 300		
Cable	Silicone	•	•	•	•	•	•	•	•	•	•	•	•	•	•		
	Teflon																
Cable length (m)	0.6	0.4	1.5	1.5	-	-	-	-	-	-	-	0.6	-	-	-		
Probe Ø x L (mm)	3 x 120	3 x 120	3 x 120	3 x 120				3 x 200	3 x 300	3 x 400		3 x 120		3 x 120			
➤ contact					3 x 200	3 x 300	3 x 400						3 x 120				
➤ protected by glass															8 x 190		
Cat. No.	780245	799693	799588	498734	799694	799695	799696	799697	799698	799699	780339	498735	799700	799701	799702		
€ Excl. VAT	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -		

Probes

Cat. No.	Description	€ Excl. VAT
799715	Temperature probe TFX400-40	NC -
780340	Temperature sensor TFX400-150	NC -
799716	Temperature sensor TFX440	NC -
799717	Temperature probe TPX100-20	NC -
799718	Temperature probe TPX100-30	NC -
799719	Temperature probe TPX100-40	NC -
799720	Temperature probe TPX200-20	NC -
799721	Temperature probe TPX200-30	NC -
799722	Temperature probe TPX200-40	NC -
799722	Temperature probe TPX200-40	NC -
799722	Temperature probe TPX400	NC -

Cat. No.	Description	€ Excl. VAT
799714	Temperature probe TPX100	NC -
799723	Temperature probe TPX200	NC -
799724	Temperature probe TPX300	NC -

Accessories

Cat. No.	Description	€ Excl. VAT
174030	Red protective case for TFX	NC -
799713	Kit including spare battery and O-ring	NC -

EBI 11 Recorders

- Temperature or pressure monitoring of an autoclave
- Temperature range : -30 to +150°C
- Waterproof
- Various probe lengths available
- Works with Winlog software



Model	EBI 11-T230	EBI 11-T231	EBI 11-T233	EBI 11-T240	EBI 11-P100
Temperature range			-30 to +150°C		
Pressure range					1 mbar to 10000 mbar
Accuracy			± 0.1°C		± 15 mbar (1 mbar to 4000 mbar)
Resolution			0.01 °C		± 20 mbar (4001 mbar to 10000 mbar)
Memory				15000	
Sensor			Pt1000		
Recording interval					1 mbar
IP					
Dimensions Ø x H without probe (mm)			16.5 x 24		16.5 x 37
Probe Ø x L (mm)	3 x 20	3 x 50	3 x 100	1.5 x 240	-
Weight (g)				45	
Cat. No.	780553	780555	780556	780554	780557
€ Excl. VAT	NC -	NC -	NC -	NC -	NC -

Software

	Winlog light	Winlog pro	Winlog med	Winlog validation
Statistical calculation	•	•	•	•
Fo calculation		•		
Adjustment of probes		•	•	•
21 CFR part 11		•	•	•
Report creation (xls or pdf)	•	•	•	•
Delivered with interface	*	•	•	•

Cat.No	Description	€ Excl. VAT
780609	Winlog.light software delivered without interface *	NC -
780546	Winlog.pro software delivered with IF200 interface for 4 recorders	NC -
780544	Winlog.med software delivered with IF100 interface for 2 recorders	NC -
780545	Winlog.validation software delivered with IF200 interface for 4 recorders	NC -
780600	IF100 interface for 2 recorders	NC -

* IF100 interface to be added, Cat. No. 780600