

## 5-channel stand-alone recording thermometer type K

- 4 core temperatures (K-type), 1 surface temperature (infrared)
- Stand-alone recorder
- 18,000 memories
- 5 displays (T1.... T4, IR)
- Remote infrared probe
- Max, Min, Hold, Moy, ΔT°, SCAN
- Backlighting / Auto Off
- Supplied in a case with K + IR probes
- PC connection
- Software + USB cable included

Type K	- 200 °C to + 1372 °C
Accuracy	± 2°C
Infrared	- 30 °C to + 550 °C
Accuracy	± 5°C
Ratio	8 :1
Sampling rate	1 sec - 24 h
Dimensions	255 x 75 x 50 mm
Weight	350 g
Battery	6F22

Cat. No.	Description	€ Excl. VAT
095389	5-channel stand-alone recording thermometer type K	NC -



## Anemometer / hygrometer / light meter / pocket thermometer

Measure	Ranges	Resolution	Accuracy
Anemometer	km/h	1.4 to 108	0.1
	m/s	0.4 to 30	0.1
	ft/min	80 to 5970	1
	MPH	0.9 to 67	0.1
	Knots	0.8 to 58.3	0.1
Hygrometer	% RH	10 to 95 %	0.10 %
			< 70% RH : ± 4% RH ≥70% RH : + (4% rdg + 1,2% RH)
Luxmeter	Lux	0 to 2200	1
		1800 to 20000	10
	Ft-cd	0 to 204	0.1
Temperature	°C	0 to + 50	0.1
	°F	32 to 122	0.1
Temperature with type K probe (optional)	°C	- 100 to + 1300	0.1
	°F	- 148 to 2375	0.1

Cat. No.	Description	€ Excl. VAT
098499	Anemometer / hygrometer / light meter / pocket thermometer	NC -

- Dual LCD display
- Temperature - 100 to + 1300 °C
- Memory max/min
- Optional K-probe
- Dimensions : 150 x 60 x 23 mm
- Weight : 160 g
- 9V battery
- Electrical specification (23 °C ± 5 °C)

