

Gilson micropipettes

Model	PIPETMAN® Classic	PIPETMAN® G	PIPETMAN® L	PIPETMAN® M
Operating mode	Manual	Manual	Manual	Motorized
Adjustable spacing between tips	No	No	No	No
Highlights	Lightweight and robust	light and robust, low pipetting and ejection force	Balanced weight, optimised grip and very low pipetting force	Lightweight, almost no pipetting force, easy to handle, automated pipetting
Volume range	0.2 µl - 10 ml	0.2 µl - 10 ml	0.5 µl - 10 ml	0,5 µl - 10 ml
Available options	1-channel	1 channel, 8 channel, 12 channel	1 channel, 8 channel, 12 channel	1 channel, 8 channel, 12 channel
RFID tracking	No	No	Yes	No
Autoclavable parts	Lower part and ejector	Lower part and ejector	Entirely	Lower part and ejector

PIPETMAN® Classic



- **Lightweight micropipette with optimised grip**
- **Robust, made of highly resistant materials such as PVDF and stainless steel**
- **Autoclavable lower part and ejector**
- **Also available in fixed volume, find them on our website**
- **Warranty: 3 years**



Volume (µl)	Suitable tips	Increment (µl)	Cat. No.	€ Excl. VAT
0.2 - 2	D(F)L10	0.002	066001	NC -
1 - 10		0.02	066002	NC -
2 - 20	D200, DF30	0.02	066003	NC -
20 - 100	D200, DF100	0.2	066004	NC -
50 - 200	D(F)200, D(F)300	0.2	066005	NC -
200 - 1,000	D(F)1,000, D(F)1200	2	066006	NC -
1,000 - 5,000	D5,000	2	066007*	NC -
1,000 - 10,000	D10 ml	20	066008*	NC -

Available with ISO 17025 calibration certificate (Cofrac approved).

* Only compatible with Gilson tips.

PIPETMAN® Classic Kits

	PIPETMAN® Classic Micro Volume Kit	PIPETMAN® Classic Starter Kit	PIPETMAN® Classic Large Volume Kit
Includes:	1 PIPETMAN® Classic P2 (0.2-2 µl) 1 PIPETMAN® Classic P10 (1-10 µl) 1 PIPETMAN® Classic P100 (10-100 µl) + Gilson Certificates + 2 racks 96 tips PIPETMAN® DIAMOND (DFL10ST, DF100ST) + 3 SINGLE racks + 1 Gilson pipetting guide	1 PIPETMAN® Classic P20 (2-20 µl) 1 PIPETMAN® Classic P200 (50-200 µl) 1 PIPETMAN® Classic P1,000 (200-1,000 µl) + Gilson Certificates + 2 racks 96 tips PIPETMAN® DIAMOND (D200, D1,000) + 3 SINGLE racks + 1 Gilson pipetting guide	1 PIPETMAN® Classic P5,000 (1,000-5,000 µl) 1 PIPETMAN® Classic P10ml (1-10 ml) + Gilson Certificates + 5 tips PIPETMAN® DIAMOND D5,000 + 2 tips PIPETMAN® DIAMOND D10 ml + 2 x 10 protective filters for P5,000 and P10 ml
Cat. No.	066085	066086	066087
€ Excl. VAT	NC -	NC -	NC -

PIPETMAN® G



- **Lightweight micropipette requiring low pipetting and ejection force**
- **Equipped with metal ejector, plastic ejector available as accessory for working with corrosive samples**
- **Robust, made of highly resistant materials such as PVDF and stainless steel**
 - **Autoclavable lower part and ejector**
 - **Warranty: 3 years**



PIPETMAN® G - Single-channel variable volume

Volume (µl)	Suitable tips	Increment (µl)	Cat. No.	€ Excl. VAT
0.2 - 2	D(F)L10	0.002	066803	NC -
1 - 10		0.02	066805	NC -
2 - 20	D200, DF30	0.02	066807	NC -
20 - 100	D200, DF100	0.2	066809	NC -
50 - 200	D(F)200, D(F)300	0.2	066811	NC -
200 - 1,000	D(F)1,000, D(F)1200	2	066813	NC -
1,000 - 5,000	D5,000	2	066814**	NC -
1,000 - 10,000	D10 ml	20	066815**	NC -

Available with ISO 17025 calibration certificate (Cofrac approved).

** Only compatible with Gilson tips, model without ejector.

PIPETMAN® G - Multi-channel variable volume

Volume (µl)	Suitable tips	Increment (µl)	8-channel		12-channel	
			Cat. No.	€ Excl. VAT	Cat. No.	€ Excl. VAT
1 - 10	D(F)L10	0.02	400083	NC -	400084	NC -
2 - 20	D(F)L10, D200, DF30	0.02	400086	NC -	400087	NC -
20 - 200	D(F)200, D(F)300	0.2	400088	NC -	400089	NC -
20 - 300		0.2	400090	NC -	400091	NC -

Available with ISO 17025 calibration certificate (Cofrac approved).