

Microwtube® seal lip screw cap Simport® (continued)

	For insert with clip								
For insert with clip									
Volume (ml)	0.5			1.5					
Diameter (mm)	11								
Height (mm)	44								
Material	Polypropylene								
Sterile	No	Yes	Yes	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip								
Autoclavable	Yes without cap								
Max centrifugal speed (g)	17000	17000	17000	20000	20000	20000	17000	17000	17000
Skirt	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes	No	No	Yes
Marking area	No	No	Yes	No	No	Yes	No	No	Yes
Operating temperature	-196 °C to +121 °C								
Specifications	Contamination-free, leak-proof sealing lip cap; free of release agents, plasticizers and biocides; free of DNases, RNases, DNA, endotoxins; tested at 95 kPa								
Units/box	1000 Microtubes	500 Microtubes	500 Microtubes	1000 microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes
Cat. No. natural	039313	039314	039315	039319	039320	039321	039316	039317	039318
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -

	For insert with clip					
For insert with clip						
Volume (ml)	2					
Diameter (mm)	11					
Height (mm)	44					
Material	Polypropylene					
Sterile	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip					
Autoclavable	Yes without cap					
Max centrifugal speed (g)	20000	20000	20000	17000	17000	17000
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes
Marking area	No	No	Yes	No	No	Yes
Operating temperature	-196 °C to +121 °C					
Specifications	Contamination-free, leak-proof sealing lip cap; free of release agents, plasticizers and biocides; free of DNases, RNases, DNA, endotoxins; tested at 95 kPa					
Units/box	1000 microtubes	500 microtubes	500 microtubes	1000 microtubes	500 microtubes	500 microtubes
Cat. No. natural	039324	039325	039326	039322	039342	039323
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -