

Microwtube® With seal screw cap Simport®

	For insert								
For insert									
Volume (ml)	0.5			1.5					
Diameter (mm)	11								
Height (mm)	44								
Material	Polypropylene								
Sterile	No	Yes	Yes	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip								
Autoclavable	Yes								
Max centrifugal speed (g)	17000	17000	17000	20000	20000	20000	17000	17000	17000
Skirt	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes	No	No	Yes
Marking area	-	-	Yes	-	-	Yes	-	-	Yes
Operating temperature	-196 °C to +121 °C								
Specifications	Cap with seal for a perfect seal; no release agents, plasticizers or biocides; Free of DNase, Rnase, DNA and endotoxins; Tested at 95 KPa								
Units/box	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes
Cat. No. natural	039296	039297	039298	039301	039302	039272	039299	039300	039271
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -

	For insert					
For insert						
Volume (ml)	2					
Diameter (mm)	11					
Height (mm)	44					
Material	Polypropylene					
Sterile	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip					
Autoclavable	Yes					
Max centrifugal speed (g)	20000	20000	20000	17000	17000	17000
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes
Marking area	-	-	Yes	-	-	Yes
Operating temperature	-196 °C to +121 °C					
Specifications	Cap with seal for a perfect seal; no release agents, plasticizers or biocides; Free of DNase, Rnase, DNA and endotoxins; Tested at 95 KPa					
Units/box	1000 microtubes	500 microtubes	500 microtubes	1000 microtubes	500 microtubes	500 microtubes
Cat. No. natural	039305	039306	039274	039303	039304	039273
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -