

## Micrewtube® With seal screw cap Simport®

	For insert with clip								
For insert with clip									
Volume (ml)	0.5			1.5					
Diameter (mm)	11								
Height (mm)	44								
Material	Polypropylene								
Sterile	No	Yes	Yes	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip								
Autoclavable	Yes								
Max centrifugal speed (g)	17000	17000	17000	20000	20000	20000	17000	17000	17000
Skirt	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes	No	No	Yes
Marking area	-	-	Yes	-	-	Yes	-	-	Yes
Operating temperature	-196 °C to +121 °C								
Specifications	Cap with seal for a perfect seal; no release agents, plasticizers or biocides; Free of DNase, Rnase, DNA and endotoxins; Tested at 95 KPa								
Units/box	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes
Cat. No. natural	039258	039282	039283	039260	039288	039289	039259	039285	039286
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -

	For insert with clip					
For insert with clip						
Volume (ml)	2					
Diameter (mm)	11					
Height (mm)	44					
Material	Polypropylene					
Sterile	No	Yes	Yes	No	Yes	Yes
Caps	Yes screw with sealing lip					
Autoclavable	Yes					
Max centrifugal speed (g)	20000	20000	20000	17000	17000	17000
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes
Marking area	-	-	Yes	-	-	Yes
Operating temperature	-196 °C to +121 °C					
Specifications	Cap with seal for a perfect seal; no release agents, plasticizers or biocides; Free of DNase, Rnase, DNA and endotoxins; Tested at 95 KPa					
Units/box	1000 microtubes	500 microtubes	500 microtubes	1000 microtubes	500 microtubes	500 microtubes
Cat. No. natural	039257	039294	039295	039256	039291	039292
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -