


















Microwtube® with tamper-proof screw cap and seal Simport®

	Tamper-proof								
									
Volume (ml)	0.5			1.5					
Diameter (mm)	11								
Height (mm)	44								
Material	Polypropylene								
Sterile	No	Yes	Yes	No	Yes	Yes	No	Yes	Yes
Caps	Yes With screw and seal								
Autoclavable	Yes								
Max centrifugal speed (g)	17000	17000	17000	20000	20000	20000	17000	17000	17000
Skirt	Yes	Yes	Yes	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes	No	No	Yes
Marking area	No	No	Yes	No	No	Yes	No	No	Yes
Operating temperature	-196 °C to +121 °C								
Specifications	Tamperproof closure; free of release agents, plasticizers and biocides; free of DNases, DNA RNases and endotoxins								
Units/box	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes	1000 Microtubes	500 Microtubes	500 Microtubes
Cat. No. natural	040214	040213	040212	040220	040219	040218	040217	040216	040215
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -

	Tamper-proof					
						
Volume (ml)	2					
Diameter (mm)	11					
Height (mm)	44					
Material	Polypropylene					
Sterile	No	Yes	Yes	No	Yes	Yes
Caps	Yes With screw and seal					
Autoclavable	Yes					
Max centrifugal speed (g)	20000	20000	20000	17000	17000	17000
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	No	Yes	No	No	Yes
Marking area	No	No	Yes	No	No	Yes
Operating temperature	-196 °C to +121 °C					
Specifications	Tamper-evident closure; free of release agents, plasticizers and biocides; free of DNases, DNA RNases and endotoxins					
Units/box	1000 microtubes	500 microtubes	500 microtubes	1000 microtubes	500 microtubes	500 microtubes
Cat. No. natural	040226	040225	040224	040223	040222	040221
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -