

# 5 ML SCREW CAP TUBES

## Greiner Bio-One 5 ml screw cap tubes



Volume (ml)	5	
Diameter (mm)	17.63	
Height (mm)	63.53	
Material	Polypropylene	
Sterile	No	Yes
Autoclavable	Yes	
Max centrifugal speed (g)	25000 g	
Graduation	Yes	
Marking area	Yes	
Operating temperature	-80 °C to +121 °C	
Specifications	Free of DNases, RNases, human DNA and pyrogens	
<b>Units/box</b>	5 bags of 100 tubes	10 bags of 50 tubes
<b>Cat. No. blue cap</b>	<b>725201</b>	<b>725261</b>
<b>€ Excl. VAT/box</b>	<b>NC -</b>	<b>NC -</b>

## Simport® 5 ml Tubes, screw cap



Volume (ml)	5	
Diameter (mm)	16	
Height (mm)	62.5	
Material	Polypropylene	
Sterile	No	Yes
Caps	Without	Screw cap; With clip; pierceable
Autoclavable	Yes	
Max centrifugal speed (g)	25000	
Graduation	Yes	
Marking area	Yes on tube and cap	
Operating temperature	-196 °C to +121 °C	
Specifications	Free of DNases, RNases, human DNA, and pyrogens; free of release agents and biocides	
<b>Units/box</b>	2 bags of 100 tubes	10 bags of 20 tubes
<b>Cat. No. single tube natural</b>	<b>040939</b>	<b>040941</b>
<b>Cat. No. amber tube only</b>	<b>040940</b>	<b>040942</b>
<b>€ Excl. VAT/box</b>	<b>NC -</b>	<b>NC -</b>

## Screw caps for 5ml tubes



Cap Type	Screw without tethered closure; drillable	Screw with tethered closure; drillable
Autoclavable	No	
Material	High density polyethylene	
Specifications	Without tethered closure	With tethered closure
<b>Units/box</b>	2 bags with 100 Plugs	
Natural	<b>040943</b>	<b>040950</b>
White	<b>040947</b>	<b>040954</b>
Yellow	<b>040948</b>	<b>040955</b>
Red	<b>040946</b>	<b>040953</b>
Green	<b>040945</b>	<b>040952</b>
Blue	<b>040944</b>	<b>040951</b>
Amber	<b>040949</b>	<b>040956</b>
<b>€ Excl. VAT/box</b>	<b>NC -</b>	<b>NC -</b>

## Inserts

Blue	Green	Lilac	Red	Yellow	Units/bag	Units/box	€ Excl. VAT/box	2D	Units/bag	Units/box	€ Excl. VAT/box
040958	040959	040960	040961	040962	100	500	NC -	040957	100	500	NC -

## 5 ml screw cap tubes



Volume (ml)	5		
Out diameter (mm)	17.63		
Height (mm)	63.53		
Material	Virgin polypropylene		
Sterile	No	Yes	Yes
Autoclavable	No		
Max centrifugal speed (g)	25000 g		
Graduation	Yes ; 0,2 ml increment		
Marking area	Yes		
Operating temperature	-86 °C to +110 °C		
Specifications	Free of DNases, RNases		
<b>Units/box</b>	5 bags of 500 tubes	10 polystyrene racks of 50 tubes	
<b>Cat. No. Black cap</b>	-	-	<b>062987</b>
<b>Blue cap Cat. No.</b>	<b>062627</b>	<b>062628</b>	-
<b>€ Excl. VAT/box</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>