

## Pyrex® Caps with tubing connection

- For the safe transfer of liquids within a closed and sterile system
- With cap and pouring ring
- Polypropylene screw cap with 2 or 3 connection ports
- GL45 thread
- Interchangeable components with 2-port and 3-port screw caps
- Autoclavable at 140°C



| Cat. No. | Description                                                           | Units/box | €/box |
|----------|-----------------------------------------------------------------------|-----------|-------|
| 002022   | GL45 Screw cap with 2 GL14 connection ports                           | 2         | NC -  |
| 002023   | GL45 Screw cap with 3 GL14 connection ports                           | 2         | NC -  |
| 002025   | GL14 Screw cap with tubing outlet                                     | 1         | NC -  |
| 002026   | GL14 Screw cap with PTFE coated insert                                | 1         | NC -  |
| 002029   | Insert for GL14 screw cap with 1.6 mm tubing outlet                   | 1         | NC -  |
| 002030   | Insert for GL14 screw cap with 3.0 mm tubing outlet                   | 1         | NC -  |
| 002031   | Insert for GL14 screw cap with 3.2 mm tubing outlet                   | 1         | NC -  |
| 002032   | Insert for GL14 screw cap with 6.0 mm tubing outlet                   | 1         | NC -  |
| 002033   | Pressure compensation set for GL14 ports (incl. 0.2µm syringe filter) | 1         | NC -  |
| 002034   | Spare 0.2µm syringe filter                                            | 2         | NC -  |

## DURAN® Caps, GLS80 with tubing connection

- Polypropylene caps with 4 ports for GLS80 modular wide neck bottles
- With tubing connection
- Safe and sterile transfer of liquids



| Cat.No. | Description                                     | Units/box | €/box |
|---------|-------------------------------------------------|-----------|-------|
| 091833B | GLS 80 Screw cap 4 GL18 ports, in PP            | 2         | NC -  |
| 091834  | Insert for GL 18 screw cap, 3.2 mm              | 1         | NC -  |
| 091835  | Insert for GL 18 screw cap, 6 mm                | 1         | NC -  |
| 091836  | Insert for GL 18 screw cap, 8 mm                | 1         | NC -  |
| 091837  | Insert for GL 18 screw cap, 10 mm               | 1         | NC -  |
| 091838  | Insert for GL 18 screw cap, 12 mm               | 1         | NC -  |
| 091839  | Blue screw cap for GL 18 tubing                 | 2         | NC -  |
| 091998  | Blanking screw cap, red, PBT GL18               | 2         | NC -  |
| 091840  | Pressure equalisation cap set for 4-port, GL 18 | 1         | NC -  |

## Screw caps GL with 2 hose connectors

The hose connection system has been developed especially for the connection of flexible tubes.

- Grey polypropylene cap center rotates freely
- For the transfer of liquid within a closed system
- Ideal for use with soft elastic tubing with inner diameter of 6-9 mm (Viton, Tygon, silicone)
- The two polypropylene connectors have angled top and straight underside connectors
- The angled hose connectors prevent the tubes from bending
- Optional sterile pressure compensation filter available
- Withstands up to + 140°C
- Autoclavable



| Cat. No. | Description                                             | Units/box | €/box |
|----------|---------------------------------------------------------|-----------|-------|
| 096000   | GL 45 Screw cap with 2 hose connectors with EPDM gasket | 2         | NC -  |
| 092046   | Pressure compensation filter                            | 2         | NC -  |

See PP GL45 caps for temperature sensors on [dulis.nl](http://dulis.nl)

