

Parafilm stretch film



006787

Stretch film especially for sealing laboratory containers.

- Thickness : 200 µm
- Liquid-tight, gas-permeable
- Operating temperature : -10 °C to +60 °C
- Supplied on a roll in a cardboard dispenser

Width (cm)	5	10	10	50
Length (m)	75	38	75	15
Cat. No.	090261	090260	090998	090999
€	NC -	NC -	NC -	NC -

Acrylic dispenser for Parafilm with cutter

Acrylic dispenser for one Parafilm roll.

- Replaceable cutting blade
- Hinged lid
- For 1 roll 10 cm or 2 rolls 5 cm

Colours	Description	€
006787	Acrylic dispenser for Parafilm with cutter	NC -

Dispenser for Parafilm with cutter

Dispenser with slider cutter and rotary film feed button.

- Clean, neat, practical
- For 5 and 10 cm wide rolls

Cat. No.	Description	€
090997	Cutter dispenser for Parafilm	NC -



Parafilm Dispenser



For the distribution of 50 or 100 mm wide rolls.

Cat. No.	Description	€
037770	Blue dispenser	NC -
320049	Green dispenser	NC -
320050	Red dispenser	NC -
037771	Replacement cutting blades (5 units)	NC -

Saran Waterproof film



Waterproof film for quick closure of containers.

- No folds, no glue
- On a roll
- Protects the user from toxic products, contaminants
- Thickness : 10 µm

Cat. No.	Description	L x W (m)	€ the roll
090264	Saran standard thickness 10 µm	300 x 0.29	NC -

Filmpro Stretch film



Stretch film for instant closure of all containers.

- Economical, in rolls
- Thickness 10 µm

L x W (m)	Without ruler		With ruler	
	Cat. No.	€ the roll	Cat. No.	€ the roll
300 x 0.3	039408	NC -	039458	NC -
300 x 0.45	039409	NC -	039459	NC -

Sealing tape for bottles



Stretch tape for reinforced sealing of laboratory bottles.

- Waterproof
- Good chemical and temperature resistance
- In rolls of 35 m
- Width : 19 mm

Colours	White	Yellow	Red	€ the roll
Cat. No.	053083	053081	053082	NC -

Petri dish closure tape



Stretchable adhesive tape for sealing and closing Petri dishes and microplates.

- Limits the risk of evaporation
- Reduces gas exchange and the risk of contamination
- Width : 12,7 mm, length: 35 m
- Good solvent resistance, waterproof
- Operating temperatures : de - 30 °C to + 70 °C

Colours	Transparent	White	Yellow	Blue	€ the roll	
Cat. No.	053001	053002	053003	053004	053005	NC -