

CIMAREC + heating plates

- Digital temperature display
- Temperature adjustable in 1 °C increments
- Indicator light when the temperature of the plate exceeds 50 °C
- Warranty: 3 years

| | | | | |
|-----------------------------|-------------------|-------------------|----------------|-------------------|
| Temperature range | 30 - 540 °C | 30 - 540 °C | 30 - 300 °C | 30 - 400 °C |
| Temp. accuracy | ± 5 °C | | | |
| Temperature uniformity | ± 2 °C | | | |
| Plate material | Ceramic | Ceramic | Aluminium | Ceramic |
| Plate dimensions W x D (mm) | 108 x 108 | 184 x 184 | 184 x 184 | 260 x 260 |
| Dimensions W x D x H (mm): | 127 x 254 x 91 | 208 x 330 x 97 | 208 x 330 x 97 | 287 x 411 x 102 |
| Weight (kg) | 2.5 | 4.3 | 4.2 | 5.4 |
| Power supply | 220-240 V / 1.6 A | 220-240 V / 4.4 A | | 220-240 V / 4.6 A |
| Cat. No. | 078529B | 078530B | 078531B | 078532B |
| € | N/A - | N/A - | N/A - | N/A - |

Thermo
SCIENTIFIC



SUPER NUOVA + hot plates

- Digital display of target and current temperature settings and timer
- Programmable with parameter memory
- Temperature adjustable in 1 °C increments
- Indicator light when the temperature of the plate exceeds 50 °C
- Supplied with PT1000 temperature sensor and stand
- Warranty: 3 years

| | | | |
|-----------------------------|-------------------|----------------|-------------------|
| Temperature range | 30 - 450 °C | 30 - 300 °C | 30 - 400 °C |
| Temp. accuracy | ± 5 °C | | |
| Temperature uniformity | ± 2 °C | | |
| Plate material | Ceramic | Aluminium | Ceramic |
| Plate dimensions W x D (mm) | 184 x 184 | 184 x 184 | 260 x 260 |
| Dimensions W x D x H (mm): | 208 x 330 x 97 | 208 x 330 x 97 | 287 x 411 x 102 |
| Weight (kg) | 4.3 | 4.2 | 5.4 |
| Power supply | 220-240 V / 4.4 A | | 220-240 V / 4.6 A |
| Cat. No. | 078533B | 078534B | 078535B |
| € | N/A - | N/A - | N/A - |

Thermo
SCIENTIFIC



MultiMagStir Genie™ Multi-position stirrer

- Stirrer for 4 containers - and for cell culture
- Wide speed range, from 10 to 1200 rpm
- Stirring in intervals or reverse stirring
- Easy programming in manual or automatic mode
- Can be stored for future use
- Can be used in an environment of 0 °C to 38 °C
- All parameters, time, pause time, speed, stirring direction, speed increase are easily programmable (9 separate steps)
- Three power levels for stirring viscous liquids
- Can be used in a cold room or incubator
- 4 programming modes (manual mode allows the choice of normal or reverse agitation, and timer functions; automatic mode activates one of four user profiles stored in memory)
- Each profile allows the creation of a protocol containing up to 9 steps
- Maximum diameter of the flasks for using the stirrer with 4 flasks: 130 mm

| | |
|---------------------------------------|----------------------|
| Stirring capacity (l) | 4 containers |
| Speed (rpm) | 10-1200 |
| Dimensions L x W x H (mm) / Peso (kg) | 375 x 325 x 48 / 3.2 |
| Permissible amb. T° (°C) | 0 to 38 |
| Cat. No. | 079061 |
| € | N/A - |

