

Baher boiling bath



For adjustable temperatures from 30 °C to 100 °C. Stability ± 3 °C.

- Fast kettle type (6 to 7 minutes)
- Stainless steel bowl and heating element
- Epoxy coated base
- Thermostat regulator with synchronised switch with signal lamp

| | |
|--------------------------------------|-------------------------|
| Capacity (litres) | 1 |
| Useful / external dimensions (ø x H) | 14 x 11 cm / 15 x 19 cm |
| Consumption (W) | 640 |
| Weight (kg) | 1 |
| Cat. No. | 068571 |
| € | N/A - |

Stainless steel accessories

| Cat. No. | Description | € |
|---------------|---|-------|
| 068572 | Rack for 24 haemolysis tubes, up to ø 13 mm | N/A - |
| 068573 | Rack for 24 haemolysis tubes, up to ø 18 mm | N/A - |
| 068574 | Lid with Bakelite handle | N/A - |
| 068575 | Resistance cover plate | N/A - |

Transparent methacrylate tanks



- Can withstand temperatures up to 60 °C
- Used with thermostats fixed with clips or clamps

| Cat. No. | Capacity (l) | H x W x D (cm) | Wall thickness (mm) | € |
|---------------|--------------|------------------|---------------------|-------|
| 068577 | 8 | 15 x 18 x 31 | 6 | N/A - |
| 068578 | 9.5 | 14.5 x 16.5 x 39 | 6 | N/A - |
| 068579 | 13 | 15 x 23 x 40 | 8 | N/A - |
| 068580 | 30 | 20 x 30 x 50 | 8 | N/A - |

Stainless steel tanks



Metal tanks for thermostat. Double wall. Stainless steel AISI 304 exterior and AISI 310 interior.

| Cat. No. | Vol. (l) | Handles + tap | Int. H x W x D (cm) | Ext. H x W x D (cm) | Weight (kg) | € |
|---------------|----------|---------------|---------------------|---------------------|-------------|-------|
| 068524 | 9 | No | 15 x 29 x 22 | 20 x 34 x 28 | 3.5 | N/A - |
| 068525 | 12 | No | 15 x 30 x 31 | 20 x 37 x 35 | 4.3 | N/A - |
| 068526 | 20 | Yes | 15 x 48 x 30 | 20 x 55 x 35 | 6.6 | N/A - |
| 068527 | 27 | Yes | 20 x 48 x 30 | 25 x 55 x 35 | 7.6 | N/A - |
| 068528 | 45 | Yes | 15 x 62 x 50 | 23 x 70 x 56 | 11 | N/A - |

Ballast ring



To prevent breakage and spillage
The ballast rings, covered with chemically resistant vinyl, hold the glassware in the water baths, preventing breakage and spillage. Closed ring (red) or open ring (blue).

| Weight (g) | Out. ø (mm) | Inner ø (mm) | Ideal for | Closed red | | Open blue | |
|------------|-------------|--------------|---------------------|---------------|-------|---------------|-------|
| | | | | Cat. No. | € | Cat. No. | € |
| 165 | 51 | 19 | Test tubes 5-10 ml | 085860 | N/A - | - | - |
| 237 | 76 | 43 | Flasks 125-500 ml | 085861 | N/A - | 037626 | N/A - |
| 454 | 89 | 51 | Flasks 250-1000 ml | 085862 | N/A - | 037627 | N/A - |
| 681 | 102 | 56 | Flasks 500-2000 ml | 085863 | N/A - | 037628 | N/A - |
| 908 | 114 | 71 | Flasks 1000-4000 ml | 085864 | N/A - | 037629 | N/A - |

Accessory

| Cat. No. | Description | € |
|---------------|---|-------|
| 085865 | Storage rack for rings (Height: 220 mm) | N/A - |

Ballast thread



Flexible and adaptable
Ballast thread coated in flexible vinyl. It can be easily twisted to adopt the desired positions.

| Cat. No. | Description | ø (mm) | € |
|---------------|--------------------|--------|-------|
| 085866 | Ballast wire 114 g | 6.4 | N/A - |
| 085867 | Ballast wire 176 g | 8 | N/A - |