

Unispense Elite peristaltic pump



- ▶ Peristaltic pump for liquid dispensing from 20.4 to 1746 ml/min.
- ▶ Possibility of adding a pedal control
- ▶ 5" LCD screen with multilingual display
- ▶ Adjustable speed from 0.5 to 400 rpm (flow rate will depend on hose diameter)
- ▶ Fully autoclavable tubing
- ▶ Up to 2 stackable heads

| Tubes | Flow rate (speed 0.5 to 400 rpm) |
|----------|----------------------------------|
| 2 mm | 20.4 to 174 ml/min |
| 3 mm | 40.2 to 354 ml/min |
| 6 mm | 131 to 1176 ml/min |
| 8 mm | 200 to 1746 ml/min |
| Accuracy | +/- 1 % |

| Cat. No. | Description | € |
|----------|---|-------|
| 050704 | Omnispense Elite peristaltic pump | N/A - |
| 050398 | Pump head "stackable" | N/A - |
| 050501 | Foot pedal | N/A - |
| 050705 | 2 mm tubing with ends 1.5 m | N/A - |
| 374311 | 3 mm tubing with ends 1.5 m | N/A - |
| 048819 | 6 mm tubing with ends 1.5 m | N/A - |
| 048815 | 8 mm tubing with ends 1.5 m | N/A - |
| 050706 | 2 mm tube for Unispense/Omnispense 7.62 m | N/A - |
| 050707 | 3 mm tube for Unispense/Omnispense 7.62 m | N/A - |
| 050708 | 6 mm tube for Unispense/Omnispense 7.62 m | N/A - |
| 050709 | 8 mm tube for Unispense/Omnispense 7.62 m | N/A - |

Antlia Digital Peristaltic Pump



- ▶ High precision and robustness
- ▶ Memory of last settings in case of power failure
- ▶ Accepts tubing with an internal diameter of less than 2.54 mm
- ▶ 12 rollers for unparalleled flow stability

| Model | Antlia-3C |
|-----------------------------|----------------------|
| Number of channels | 3 |
| Speed (rpm) | 0.5 to 50 |
| Increment (rpm) | 0.1 |
| Stability (rpm) | 0.01 |
| Minimum flow rate (mL/min) | 0.004 |
| Head diameter (mm) | 70 |
| Roll (No. / material) | 12 / stainless steel |
| Dimensions (W x L x H) (mm) | 170 x 170 x 250 |
| Weight (kg) | 5.5 |
| Power supply | 90-264V, 47-440 Hz |
| Cat. No. | 178961 |
| € | N/A - |